

234-235 LAME CIRCOLARI UNIVERSALI

UNIVERSAL CIRCULAR SAW BLADES ALTERNATE TOOTH

234 234S

Codice nr. HW	D.	B/b	d.	Z	FT
	mm.	mm.	mm.		
234 20	200	3.2/2.2	30	24	
234 25S	250	3.2/2.2	30	30	2/7/42+2/10/60
234 30S ●	300	3.2/2.2	30	36	2/7/42+2/10/60
234 35S ●	350	3.6/2.5	30	42	2/7/42+2/10/60
234 40S	400	4.0/2.8	30	48	2/7/42+2/10/60
234 45	450	4.2/3.0	30	54	2/10/60
234 50	500	4.2/3.0	30	60	2/10/60
234 55	550	5.2/3.6	30	60	2/10/60
234 60	600	5.2/3.6	30	60	2/10/60




AFFILATURA ALTERNATA CON DENTI IN HW PER TAGLI TRASVERSALI PER LEGNO NATURALE, IMPIALLACCIATI E COMPENSATI.

ALTERNATE TOOTH WITH POSITIVE ANGLE TIPS IN HW FOR CROSS CUTTING OF SOFT AND HARD WOOD, PLYWOOD AND VEENERS.

● PRONTO A MAGAZZINO - IN STOCK


S = SILENZIATE - LOW NOISE

DS = DOPPIA SILENZIATURA
- ULTRA LOW NOISE



235 235S 235DS

Codice nr. HW	D.	B/b	d.	Z	FT
	mm.	mm.	mm.		
235 20	200	3.2/2.2	30	34	
235 25S	250	3.2/2.2	30	40	2/7/42+2/10/60
235 30S ●	300	3.2/2.2	30	48	2/7/42+2/10/60
235 35S ●	350	3.6/2.5	30	54	2/7/42+2/10/60
235 40S	400	4.0/2.8	30	60	2/7/42+2/10/60
235 45	450	4.2/3.0	30	66	2/10/60
235 50	500	4.2/3.0	30	72	2/10/60
235 55	550	5.2/3.6	30	80	2/10/60
235 60	600	5.2/3.6	30	80	2/10/60



AFFILATURA ALTERNATA CON DENTI IN HW PER TAGLI TRASVERSALI PER LEGNO NATURALE, IMPIALLACCIATI E COMPENSATI.

ALTERNATE TOOTH WITH POSITIVE ANGLE TIPS IN HW FOR CROSS CUTTING OF SOFT AND HARD WOOD, PLYWOOD AND VEENERS.